

RC200 Keyfob

Technical specifications



1. Electrical characteristics

Parameter	Value
Power supply	1 battery
Battery type	Lithium 3.0 V RC2
Battery life	9 years or 15000 pushes
Battery level indicator	Yes, transmitted to the panel
Communication	
Type	Fully wireless
Technology	WiseLink®
Radio type	Bi directional
Frequency	FM 868 Mhz in 4 bands
Frequency allocation	Automatic by the panel
Transmission speed	9600 bds
Supervision	No
Antenna	Integrated
Transmission security	By AES encryption algorithm
Approval	CE Marking
Operating temperature	0°C ...+40°C
Shocks	IK07
Protection	IP30
Humidity	70% max

2. Functionalities

Parameter	Value
Nb keys	4
Functions	ON : total arming OFF : total disarming SP1 : partition 1 (programmable) SP2 : partition 2 (programmable) PANIC 1 : by pressing SP1 for 5 sec PANIC 2 : by pressing SP2 for 5 sec
Acknowledgement (way back)	Yes by Buzzer indicating the panel reception
Recording	By using 2 buttons simultaneously
Traceability	Internal serial nb, and bar code
Tamper protection	No

3. Mechanical characteristics

Parameter	Value
Material	ABS- ULV0
Height	84 mm
Length	40 mm
Thickness	17 mm
Weight (without battery)	32g
Packaging	Individual